

ABS UPRIGHT CHILLER (Solid door)

Technical Data

Model	SR200TN	SR400TN	SR600TN
Capacity Gross (L)	96	296	526
Capacity Net (L)	67.6	238.6	452.8
Climate Class	Class 4/30℃/55%RH	Class 4/30℃/55%RH	Class 4/30℃/55%RH
Energy Class	A	C	C
Noise Level (dB)	52	54	58
Dimension / Weight			
Internal Dimension (mm)	457 × 474 × 600	457 × 474 × 1600	632 × 610 × 1600
External Dimension (mm)	600 × 625 × 850	600 × 625 × 1860	775 × 760 × 1860
Packing Dimension (mm)	640 × 660 × 890	640 × 705 × 2000	820 × 760 × 2000
Product volume	0.32	0.7	1.08
Net Weight (kgs)	38	69	90
Gross Weight (kgs)	41	82	106
Specification			
Temperature Range (℃)	0-10	0-10	0-10
Refrigerant GAS	R600a	R600a	R600a
Refrigerant Charge (g)	35	40	52
Cooling system	Static	/	/
Defrost System	By time	By time	By time
Hot gas valve	N/A	N/A	N/A
Thermostat	Dixell XR02CX	Dixell XR02CX	Dixell XR02CX
Compressor	HUAYI, HYB69MHUa	HUAYI, HYB96MHUa	HUAYI, HYS113MCA
Defrost power (W)	N/A	N/A	N/A
Rated Power consumption (W)	120	155	180
Voltage Supply (V/Hz)	220V~240V/50Hz	220V~240V/50Hz	220V~240V/50Hz
Rated Current (A)	0.8	1.1	1.2
Energy consumption (Kwh/24h)	1.069	1.106	1.629
Light	N/A	N/A	N/A
Total light power (W)	N/A	N/A	N/A
Structure			
Glass Type	/	/	/
Self closing Door	No	Yes	Yes
lock and key	Yes	Yes	Yes
Shelf Size (mm)	477 × 423 × 2pcs 477 × 207 × 1pcs	477 × 423 × 4pcs 477 × 207 × 1pcs	652 × 554 × 4pcs 652 × 347 × 1pcs
Shelf bear weight (kg)	20	20	20

Product Certification



* We have the right to change the product design and configuration without informing customers in advance!



SR200TN/G

SR400TN/G

SR600TN/G

Product Details

