

ABS UPRIGHT FREEZER (Solid door)

Technical Data

Model	SR200BT	SR400BT	SR600BT
Capacity Gross (L)	96	296	526
Capacity Net (L)	72.4	256.2	471
Climate Class	Class 4/30°C/55%RH	Class 4/30°C/55%RH	Class 4/30°C/55%RH
Energy Class	A	C	B
Noise Level (dB)	62	64	68
Dimension / Weight			
Internal Dimension (mm)	457 × 474 × 600	457 × 474 × 1600	632 × 610 × 1600
External Dimension (mm)	600 × 625 × 850	600 × 625 × 1860	775 × 760 × 1860
Packing Dimension (mm)	640 × 660 × 890	640 × 705 × 2000	820 × 760 × 2000
Product volume	0.32	0.7	1.08
Net Weight (kgs)	39	69	93
Gross Weight (kgs)	42	82	108
Specification			
Temperature Range (°C)	-22~-15	-22~-15	-22~-15
Refrigerant GAS	R600a	R290	R290
Refrigerant Charge (g)	29	63	92
Cooling system	Static	Static	/
Defrost System	By temperature	By temperature	By time
Hot gas valve	N/A	N/A	N/A
Thermostat	Dixell XR02CX	Dixell XR02CX	Dixell XR02CX
Compressor	HUAYI, HYB96MHUa	CUBIGEL, NFH70NA	CUBIGEL, NFG80NA
Defrost power (W)	N/A	N/A	N/A
Rated Power consumption (W)	130	200	260
Voltage Supply (V/Hz)	220V~240V/50Hz	220V~240V/50Hz	220V~240V/50Hz
Rated Current (A)	1	1.4	1.8
Energy consumption (Kwh/24h)	1.869	2.996	3.364
Light	N/A	N/A	N/A
Total light power (W)	N/A	N/A	N/A
Structure			
Glass Type	/	/	/
Self closing Door	No	Yes	Yes
lock and key	Yes	Yes	Yes
Shelf Size (mm)	468 × 405 × 2pcs 468 × 186 × 1pcs	468 × 405 × 6pcs 468 × 186 × 1pcs	643 × 564 × 6pcs 643 × 319 × 1pcs
Shelf bear weight (kg)	20	20	20

Product Certification



* We have the right to change the product design and configuration without informing customers in advance!



Product Details

