

ABS UPRIGHT CHILLER (Glass door)

Technical Data

Model	SR200TN/G	SR400TN/G	SR600TN/G
Capacity Gross (L)	96	296	526
Capacity Net (L)	67.6	238.6	452.8
Climate Class	Class 3/25℃/60%RH	Class 3/25℃/60%RH	Class 3/25℃/60%RH
Energy Class	A	D	D
Noise Level (dB)	45	47	50
Dimension / Weight			
Internal Dimension (mm)	457.5 × 474 × 601	457.5 × 474 × 1601	632.5 × 610 × 1601
External Dimension (mm)	600 × 625 × 850.5	600 × 625 × 1860.5	775 × 760.5 × 1860.5
Packing Dimension (mm)	640 × 660 × 890	640 × 705 × 2000	820 × 760 × 2000
Product volume	0.37	0.84	1.3
Net Weight (kgs)	45	84	108
Gross Weight (kgs)	48.5	96	124
Specification			
Temperature Range (℃)	2-10	2-10	2-10
Refrigerant GAS	R600a	R600a	R290
Refrigerant Charge (g)	35	60	60
Cooling system	Static	Static	Static
Defrost System	By time	By time	By time
Hot gas valve	N/A	N/A	N/A
Thermostat	OMKJ, OM-140	OMKJ, OM-140	OMKJ, OM-140
Compressor	HUAYI, HYB69MHUa	HUAYI, HYS113MCA	CUBIGEL NFH55NA
Defrost power (W)	N/A	N/A	N/A
Rated Power consumption (W)	140	170	190
Voltage Supply (V/Hz)	220V~240V/50Hz	220V~240V/50Hz	220V~240V/50Hz
Rated Current (A)	0.9	1.1	1.3
Energy consumption (Kwh/24h)	0.723	1.276	1.597
Light	2 LED lamps	2 LED Lamps	2 LED Lamps
Total light power (W)	6w × 2	13w × 2	13w × 2
Structure			
Glass Type	Double	Double	Double
Self closing Door	No	Yes	Yes
lock and key	No	No	No
Shelf Size (mm)	477 × 423 × 2pcs 477 × 207 × 1pcs	477 × 423 × 4pcs 477 × 207 × 1pcs	652 × 554 × 4pcs 652 × 347 × 1pcs
Shelf bear weight (kg)	20	20	20

Product Certification



* We have the right to change the product design and configuration without informing customers in advance!



SR200TN/GSR400TN/GSR600TN/G

Product Details

